



FULLY AUTOMATIC SHEET DISPENSER  
SHEET DISPENSER CTFP



# Sheet Dispenser CTFP

For extra water protection, the production line can be fitted with equipment which, together with the Cyklop stretchwrapper, will also meet this requirement.

The Cyklop top film dispenser is usually included in a fully automatic line next to a stretchwrapper when palletised goods need protection from dust or dampness on top. The machine is easy to fit and made of aluminium.

A programmable logic control systems and frequency converters make the machine highly flexible and easy to customise. Among other advantages our patented method makes it possible for one person to change the film spool, as it is mounted close to the floor and does not have to be lifted above the conveyor line.

## How does it work?

The arm pulls a film sheet and applies it to the top of the palletized goods and once the goods have been stretch wrapped the top sheet is firmly wrapped in position.

## Specification and dimensions CTFP

Capacity	Up to 50-85 pallets/hour	
Film width	1200, 1600, 1800 mm	
Roll diameter	Max. 200 mm	
Top sheet length	Max. 1800 mm	
Power	Supply	3-phase, 400V+N+PE, 50 Hz, 0.4 kW
	Protection	IP54
Dimensions	Mast height	3575 mm (Std)
Pneumatics	Airpressure	6 bar
Operating temperature:	5°C (40°F) to 35°C (95°F) for use in a dry, tempered area.	
CE-mark	(EN 60204)	



CTFP



GL 1000 equipped with option CTFP, gives a protection against dust and dampness.

Crated dimensions standard machine: L4000 x W800 x H1000 mm.  
Weight 350 kg.

[WWW.CYKLOPTEKNIK.SE](http://WWW.CYKLOPTEKNIK.SE)

Subject to Modification. Protective notice pursuant to ISO 16016 to be observed. © Copyright Cyklop GmbH, Cologne, Cyklop Technik AB - PBE 961023EN - 2012